


SECUMAR Delta 150 Ferry Twin Solas approved inflatable lifejacket

The semi-circular shaped buoyancy chambers are a design-innovation and feature an unmatched compactness. This results in maximum safety for small storage space on ferries and passenger ships.

SOLAS lifejacket certified to IMO Res. MSC.81(70) amended by MSC.200(80) and MSC.207(81).



Twin buoyancy chamber

The twin chamber offers redundancy in case of a defect in the standard upper buoyancy chamber. The lower chamber can be activated if the already inflated upper chamber loses gas. The volume of the lower chamber has the same buoyancy as the upper chamber. It is not necessary to inflate extra air via the oral inflation valve.

- buoyancy chamber is divided by an internal membrane in an upper and a lower chamber
- polyurethane coated fabric
- high frequency welded (HF)
- buoyancy approx. 165 N
- 3M® retroreflecting tape (400 cm²)
- colour of buoyancy chamber: yellow
- upper chamber fully automatic inflated
- lower chamber manually inflatable
- both chambers are fitted with an oral inflation tube and integrated oral inflation valve
- upper chamber with overpressure valve

Automatic inflator SECUMATIC 3001 S/Upper chamber inflation device

- with the SECUMAR pill as the trigger element, in service for more than 30 years
- Three green indicators show readiness of the inflation device
- Unique torque safe tying system ensures proper suit of CO₂-cylinder and correct screw in
- additional manual release
- Contents of gas cylinder: 32g CO₂
- easy to reload (no tools required)

Manual inflator SECUMAR SM 301/Lower chamber inflation device

- Two green indicators show that the CO₂-cylinder is screwed in at correct torque and that the release lever is correctly fixed to the housing
- Unique torque safe tying system ensures proper suit of CO₂-cylinder and correct screw in
- gas-cylinder, contents 32g CO₂
- thread connection: UNF ½ "
- easy to reload (no tools required)

Distress Sealight

- According to SOLAS-regulations the lifejacket is equipped with the approved distress light SECULUX CXF-II.

Whistle

- The lifejacket is equipped with a two-tone-whistle with cord.

Rescue Strap

- The lifejacket is equipped with a lifting becket (320 daN lifting capacity).

Lifeline with toggle

- A lifeline with toggle is attached to the protective cover to connect to other survivors.

Instructions for use

- Each lifejacket is equipped with instructions for use.