

SIMPLE AND EFFECTIVE

With the Typhoon™, you can instantly decide to go out boating: light and compact, it easily fits in the boot of your car.

THE “+” of the PRODUCT

A removable inflatable floor: inflated at high pressure, it is as rigid and less heavy than a traditional floor! An inflatable keel: it ensures a good heading hold and provides an extra buoyancy. Semi-recessed valve and swimming platform.

TECHNICAL FEATURES

| | | | |
|-----------------------------------|--------|-----------------------------------|--------|
| EXTERNAL LENGTH | 3,60 m | AVERAGE RECOMMENDED POWER (kW) | 12 |
| INTERNAL LENGTH | 2,33 m | MAXIMUM AUTHORIZED POWER (HP) | 20 |
| EXTERNAL WIDTH | 1,74 m | MAXIMUM AUTHORIZED POWER (kW) | 15 |
| INTERNAL WIDTH | 0,88 m | MAXIMUM AUTHORIZED ENGINE WEIGHT | 52 kg |
| TUBE DIAMETER | 0,43 m | MAXIMUM SPEED (MONO) (km/h - mph) | 38-24 |
| NUMBER OF PASSENGERS (ISO) | 5 | HULL LENGTH AT THE 1st BAG (tube) | 1,20 m |
| MAXIMUM AUTHORIZED LOAD | 600 kg | HULL WIDTH AT THE 1st BAG (tube) | 0,67 m |
| TOTAL WEIGHT | 64 kg | HULL HEIGHT AT THE 1st BAG (Tube) | 0,30 m |
| NUMBER OF WATERTIGHT COMPARTMENTS | 3+1 | LENGTH OF THE 2nd BAG (floor) | 1,12 m |
| DESIGN CATEGORY | C | WIDTH OF THE 2nd BAG (floor) | 0,77 m |
| SHAFT | Court | HEIGHT OF THE 2nd BAG (Floor) | 0,15 m |
| AVERAGE RECOMMENDED POWER (HP) | 15 | | |

VERSIONS

Z55038

360 ALU

0 DKK

OPTIONS

| | | | | |
|------------------------------|----------------------|-------|-----------------|--|
| HULL & DECK | | | OTHER(S) | |
| Z61087 | Side rigid ladder | 0 DKK | Z61134 | Bag under seat 0 DKK |
| FISHING & LEISURE | | | Z61161 | Launching wheels 0 DKK |
| Z1186 | Fishing rod holder | 0 DKK | Z1084 | Manœuvre roller 0 DKK |
| SEATS | | | Z67152 | Pressure indicator valve bravo 5 0 DKK |
| Z69362 | 2nd bench grey L1100 | 0 DKK | | |